

**Composite Combinations – Sheet Grades**

<b>Composite Combinations 1/2</b>				
<b>Grade</b>	<b>NP424</b>	<b>NP615</b>	<b>NP634</b>	<b>NP900</b>
Resin – Reinforcements	Epoxy Resin – Glass Fabric & Cellulosic Paper	Melamine Resin Paper Surfaces – NP612 Core	Phenolic Resin – Glass Fabric & Cellulosic Paper	Phenolic Resin – Rubber & Cellulosic Paper
NEMA <sup>1</sup>	CEM-1	---		
Color	TN	NA/BK		NA
Sheet Size	Thickness Manufactured			
39" x 79"		0.031 - 0.250		0.031 - 0.250
39" x 48"				0.171
48" x 120"		0.031 - 0.250		
48" x 96"			0.047 - 0.250	
48" x 72"	0.025 - 0.250			
Cover Plies		XE		
48" x 96" - Thin sheets manufactured 2 <sup>nd</sup> week of the calendar month.			X	
Press load quantities required.				
Testing required.				

<sup>1</sup> For information on Specifications and Standards, see "Sheet – Specification Cross Reference".

<b>Composite Combinations – 2/2</b>	
<b>Grade</b>	<b>MC450SB (StormBlocker™)</b>
Resin – Reinforcements	Phenolic Resin – Glass Fabric & Cellulosic Products
NEMA <sup>2</sup>	---
Color	NA
Sheet Size	Thickness Manufactured
48" x 120"	Nom. = 0.312
48" x 108"	Nom. = 0.312
48" x 96"	Nom. = 0.312
Press load quantities required.	X
Minimum purchase quantity required.	X

<sup>2</sup> For information on Specifications and Standards, see "Sheet – Specification Cross Reference".