



Convolute Rolled Tube Products - Dimensional & Tolerance Data

		Minimum & Maximum Inside Diameters and Tolerances								Minimum & Maximum Outside Diameters and Tolerances										
Norplex-Micarta Grade / NEMA Grade	Inside Diameter		Inside Diameter Tolerance (+/-) (For Inside Diameter Ranges Indicated)						Outside Diameter		Outside Diameter Tolerance Ground (+/-) (For Outside Diameter Ranges Indicated)			Outside Diameter Tolerance Lathe Turned (+/-) (For Outside Diameter Ranges Indicated)				Unfinished Minimum Target (+ only) (For Outside Diameter Ranges indicated)		
			0.094" ≤ 0.749"	0.750" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"			24.001" ≤ 48.000"	0.156" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 9.000"	9.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"	9.000" ≤ 20.000"	20.001" ≤ Maximum
	Minimum	Maximum	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	Minimum	Maximum	0.156" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 9.000"	9.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"	9.000" ≤ 20.000"
RT130 / NEMA FR-4	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT130M / NEMA FR-4	0.313"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT130X / NEMA FR-4	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT500 / NEMA G-10	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT500F / NEMA G-10	0.188"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT500M / NEMA G-10	0.313"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT500X / NEMA G-10	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT504 / NEMA G-3, type	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT504F / NEMA G-3, type	0.188"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT505 / NEMA G-5	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT505F / NEMA G-5	0.188"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT507 / NEMA G-7	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT507F / NEMA G-7	0.250"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.313"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT507L / NEMA G-7	0.313"	3"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	5"	0.005"	0.008"	0.025"	N/A	N/A	N/A	N/A	N/A	N/A
RT509 / NEMA G-9	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT509F / NEMA G-9	0.188"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT511 / NEMA G-11, type	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT511F / NEMA G-11, type	0.188"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT511M / NEMA G-11, type	0.313"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT520M / NEMA G-10	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT520X / NEMA G-10	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"



Convolute Rolled Tube Products - Dimensional & Tolerance Data

Norplex-Micarta Grade / NEMA Grade	Minimum & Maximum Inside Diameters and Tolerances									Minimum & Maximum Outside Diameters and Tolerances										
	Inside Diameter		Inside Diameter Tolerance (+/-) (For Inside Diameter Ranges Indicated)							Outside Diameter		Outside Diameter Tolerance Ground (+/-) (For Outside Diameter Ranges Indicated)			Outside Diameter Tolerance Lathe Turned (+/-) (For Outside Diameter Ranges Indicated)			Unfinished Minimum Target (+ only) (For Outside Diameter Ranges indicated)		
			0.094" ≤ 0.749"	0.750" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"			0.156" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 9.000"	9.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"	9.000" ≤ 20.000"	20.001" ≤ Maximum
	Minimum	Maximum	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	Minimum	Maximum	0.156" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 9.000"	9.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"	9.000" ≤ 20.000"
RT521M / NEMA G-10	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT521X / NEMA G-10	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT571 / NEMA G-10	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	1.000"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT310 / NEMA C	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	1.000"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT315	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	1.000"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT342 / NEMA C	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.594"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB320 / NEMA LE	0.250"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.313"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB320D	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB320X / NEMA LE	0.375"	23.812"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	N/A	0.438"	24"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RTB320Z / NEMA LE	0.094"	0.938"	0.003"	0.004"	N/A	N/A	N/A	N/A	N/A	0.156"	1"	0.005"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
RTB324	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT325	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB326	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB329	0.250"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.313"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT610 / NEMA X	0.188"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT628 / NEMA XX	0.188"	24"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	26"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT629 / NEMA XX	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT630 / NEMA XXX	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"



Convolute Rolled Tube Products - Dimensional & Tolerance Data

Norplex-Micarta Grade / NEMA Grade	Wall Thicknesses by Inside Diameter												Wall Thickness Tolerances							
	Inside Diameter		Minimum And Maximum Wall Thickness (For Inside Diameter Ranges Indicated)										Inside Diameter		Wall Thickness Tolerance (+/-) (Average Wall Thickness Of Individual Tube, Measured At Any Point On The Wall)					
			0.094" ≤ 0.187"	0.188" ≤ 0.374"	0.375" ≤ 0.624"	0.625" ≤ 1.249"	1.250" ≤ 2.999"	3.000" ≤ 4.874"	4.875" ≤ 8.999"	9.000" ≤ 23.999"	24.000" ≤ 29.999"	30.000" ≤ 48.000"			0.031" ≤ 0.031"	0.032" ≤ 0.062"	0.063" ≤ 0.125"	0.126" ≤ 0.250"	0.251" ≤ 0.500"	0.501" ≤ 5.000"
RT130 / NEMA FR-4	0.750"	48"	N/A	N/A	N/A	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.750"	48"	N/A	0.008"	0.009"	0.011"	0.013"	N/A
RT130M / NEMA FR-4	0.313"	48"	N/A	0.094" - 0.250"	0.094" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.313"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT130X / NEMA FR-4	0.094"	48"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.094"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT500 / NEMA G-10	0.750"	48"	N/A	N/A	N/A	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.750"	48"	N/A	0.008"	0.009"	0.011"	0.013"	N/A
RT500F / NEMA G-10	0.188"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.188"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT500M / NEMA G-10	0.313"	48"	N/A	0.094" - 0.250"	0.094" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.313"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT500X / NEMA G-10	0.094"	48"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.094"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT504 / NEMA G-3, type	0.750"	48"	N/A	N/A	N/A	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.750"	48"	N/A	0.008"	0.009"	0.011"	0.013"	N/A
RT504F / NEMA G-3, type	0.188"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.188"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT505 / NEMA G-5	0.500"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.500"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT505F / NEMA G-5	0.188"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.188"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT507 / NEMA G-7	0.500"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.500"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT507F / NEMA G-7	0.250"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.250"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT507L / NEMA G-7	0.313"	3"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	N/A	N/A	N/A	0.313"	3"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT509 / NEMA G-9	0.500"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.500"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT509F / NEMA G-9	0.188"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.188"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT511 / NEMA G-11, type	0.750"	48"	N/A	N/A	N/A	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.750"	48"	N/A	0.008"	0.009"	0.011"	0.013"	N/A
RT511F / NEMA G-11, type	0.188"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.188"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT511M / NEMA G-11, type	0.313"	48"	N/A	0.094" - 0.250"	0.094" - 1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	1.000"	0.313"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT520M / NEMA G-10	0.375"	48"	N/A	N/A	0.094" - 1.000"	xxx	xxx	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.375"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT520X / NEMA G-10	0.094"	48"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.094"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A



Convolute Rolled Tube Products - Dimensional & Tolerance Data

Norplex-Micarta Grade / NEMA Grade	Wall Thicknesses by Inside Diameter												Wall Thickness Tolerances									
	Inside Diameter		Minimum And Maximum Wall Thickness (For Inside Diameter Ranges Indicated)										Inside Diameter		Wall Thickness Tolerance (+/-) (Average Wall Thickness Of Individual Tube, Measured At Any Point On The Wall)							
			0.094" ≤ 0.187"	0.188" ≤ 0.374"	0.375" ≤ 0.624"	0.625" ≤ 1.249"	1.250" ≤ 2.999"	3.000" ≤ 4.874"	4.875" ≤ 8.999"	9.000" ≤ 23.999"	24.000" ≤ 29.999"	30.000" ≤ 48.000"			0.031" ≤ 0.031"	0.032" ≤ 0.062"	0.063" ≤ 0.125"	0.126" ≤ 0.250"	0.251" ≤ 0.500"	0.501" ≤ 5.000"		
RT521M / NEMA G-10	0.375"	48"	N/A	N/A	0.094" - 1.000"	0.188" - 1.000"	0.375" - 1.000"	0.625" - 1.000"	1.250" - 1.000"	3.000" - 1.000"	4.875" - 1.000"	9.000" - 1.000"	24.000" - 1.000"	30.000" - 1.000"	0.375"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT521X / NEMA G-10	0.094"	48"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.094"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT571 / NEMA G-10	0.750"	48"	N/A	N/A	N/A	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.750"	48"	0.006"	0.008"	0.009"	0.011"	0.013"	N/A
RT310 / NEMA C	0.750"	48"	N/A	N/A	N/A	0.125" - 1.500"	0.125" - 1.875"	0.125" - 2.375"	0.125" - 3.000"	0.125" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.750"	48"	N/A	N/A	0.015"	0.020"	0.020"	N/A
RT315	0.750"	48"	N/A	N/A	N/A	0.125" - 1.500"	0.125" - 1.875"	0.125" - 2.375"	0.125" - 3.000"	0.125" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.750"	48"	N/A	N/A	0.015"	0.020"	0.020"	N/A
RT342 / NEMA C	0.500"	48"	N/A	N/A	0.047" - 1.000"	0.047" - 1.500"	0.047" - 1.875"	0.062" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.500"	48"	N/A	0.015"	0.015"	0.020"	0.020"	N/A
RTB320 / NEMA LE	0.250"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.250"	48"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RTB320D	0.375"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.375"	48"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RTB320X / NEMA LE	0.375"	23.812"	N/A	N/A	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - N/A	0.125" - N/A	0.125" - N/A	0.125" - N/A	0.375"	0.500"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RTB320Z / NEMA LE	0.094"	0.938"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 0.188"	0.031" - 0.063"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.094"	0.500"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RTB324	0.375"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.375"	0.500"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RT325	0.500"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.500"	48"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RTB326	0.375"	48"	N/A	N/A	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.375"	0.500"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RTB329	0.250"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.250"	0.500"	N/A	0.010"	0.011"	0.013"	0.015"	N/A
RT610 / NEMA X	0.188"	48"	N/A	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.188"	48"	0.005"	0.006"	0.007"	0.009"	0.011"	N/A
RT628 / NEMA XX	0.188"	24"	N/A	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.500"	0.031" - 1.875"	0.047" - 2.375"	0.062" - 3.000"	0.094" - 3.500"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.125" - 5.000"	0.188"	24"	0.005"	0.006"	0.007"	0.009"	0.011"	N/A
RT629 / NEMA XX	0.094"	48"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.094"	48"	0.005"	0.006"	0.007"	0.009"	0.011"	N/A
RT630 / NEMA XXX	0.094"	48"	0.031" - 0.203"	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.125" - 1.000"	0.094"	48"	0.005"	0.006"	0.007"	0.009"	0.011"	N/A