

RT360 TECHNICAL DATA BULLETIN

GRADE: RT360 NEMA LI 1-1998 GRADE: -- U.L. LISTED: N

DESCRIPTION: Grade RT360 is a tube made from a HEAVY weight canvas fabric combined with a phenolic resin that has good physical properties and machining characteristics. Typical applications include journal bearings and structural parts that require good impact strength and wear resistance.

TYPICAL PROPERTIES

		-	VALUE	
		UNITS	Specimen Tested (ID x OD)	
			2.00" x 2.50"	
PHYSICAL PROPERTIES				
Specific Gravity				
(ASTM D792)		-	1.34	
Rockwell Hardness				
(ASTM D785)		M Scale	80	
Moisture Absorption	Condition D ₁ -24/23			
(ASTM D570)		%	1.30	
Tensile Strength	Condition A			
(ASTM D638)		psi	5,500	
Compressive Strength	Condition A			
(ASTM D695)		psi	18,500	
Compressive Modulus	Condition A			
(ASTM D695)		kpsi	350	
THERMAL PROPERTIES				
Temperature Index ¹				
	Electrical / Mechanical	°C	- / 140	
Flammability Rating	Condition A			
(UL Bulletin 94)		Class	HB	

¹ NEMA LI-6: This temperature is a recommendation only, and based upon experience in various applications. The maximum operating temperature is dependent upon the application and should be investigated prior to use.

This data, while believed to be accurate and based on reliable analytical methods, is for informational purposes only. The terms and conditions of the agreement under which it is sold will govern any sales of this product. Data supplied above are "typical values"; not to be considered "specification values".

To assure the material's performance is adequate for a specific application; customers should verify, independent of Norplex-Micarta, performance characteristics of interest.

It is the responsibility of the users of this information to make sure that they have the latest version of this TDB, and are urged to contact Customer Service, or preferably our web site, www.norplex-micarta.com, to determine if information is the most current.

Specification writers: Contact Norplex-Micarta for specification values before submission.