

BT22NPN

TECHNICAL DATA BULLETIN

GRADE: BT22NPN

NEMA GRADE: --

U.L. LISTED: N

DESCRIPTION: BT22NPN is composed of an extra-fine weave woven cotton fabric combined with a phenolic resin system to produce a tube product that has superior machining capability with smooth, fiber free surfaces. Typical uses include retainers for ball-bearings and applications that require fine machining characteristics.

TYPICAL PROPERTIES

			VALUE
		UNITS	Specimen Tested (ID x OD)
			0.75″ x 1.00″
PHYSICAL PROPERTIES			
Specific Gravity			
(ASTM D792)		-	1.29
Rockwell Hardness			
(ASTM D785)		M Scale	100
Moisture Absorption (ASTM D570)	Condition D ₁ -24/23	%	1.20
Acetone Extraction (ASTM F2953-12)	Condition A	%	<1.0
Tensile Strength (ASTM D638)	Condition A	psi	10,000
Compressive Strength (ASTM D695)	Condition A	psi	30,000
Compressive Modulus (ASTM D695)	Condition A	kpsi	425



Global Thermoset Composite Solutions

BT22NPN - TYPICAL PROPERTIES (continued)

		UNITS	VALUE
			Specimen Tested (ID x OD)
			0.75" x 1.00"
THERMAL PROPERTIES			
Temperature Index ¹			
	Electrical / Mechanical	°C	125 / 125
Flammability Rating	Condition A		
(UL Bulletin 94)		Class	HB
ELECTRICAL PROPERTIES			
Electric Strength	Condition A		
(ASTM D149)		Volts/mil	190

¹ NEMA LI-6: This temperature is a recommendation only, and based upon experience in various applications. The maximum operating temperature is dependent upon the application and should be investigated prior to use.

This data, while believed to be accurate and based on reliable analytical methods, is for informational purposes only. The terms and conditions of the agreement under which it is sold will govern any sales of this product. Data supplied above are "typical values"; not to be considered "specification values".

To assure the material's performance is adequate for a specific application; customers should verify, independent of Norplex-Micarta, performance characteristics of interest.

It is the responsibility of the users of this information to make sure that they have the latest version of this TDB, and are urged to contact Customer Service, or preferably our web site, www.norplex-micarta.com, to determine if information is the most current.

Specification writers: Contact Norplex-Micarta for specification values before submission.