

BT25NPP

TECHNICAL DATA BULLETIN

GRADE: BT25NPP

NEMA GRADE: --

U.L. LISTED: N

DESCRIPTION: Grade BT25NPP is constructed of a fine weave cotton fabric which has been bleached to remove impurities, and a modified phenolic resin with powdered PTFE added for lubrication. It has low moisture absorption and excellent dimensional stability and chemical resistance. Typical uses include bearing retainers and parts that require excellent machining characteristics.

TYPICAL PROPERTIES

			VALUE	
		UNITS	Specimen Tested (ID x OD)	
			0.75" x 1.00"	
PHYSICAL PROPERT	IES			
Specific Gravity				
(ASTM D792)		-	1.27	
Rockwell Hardness				
(ASTM D785)		M Scale	100	
Moisture Absorption	Condition D ₁ -24/23			
(ASTM D570)		%	1.00	
Tensile Strength	Condition A			
(ASTM D638)		psi	8,000	
Compressive Strength	Condition A			
(ASTM D695)		psi	22,500	
Compressive Modulus	Condition A			
(ASTM D695)		kpsi	390	
THERMAL PROPERTI	IES			
Temperature Index ¹				
	Electrical / Mechanical	°C	- / 140	
Flammability Rating	Condition A			
(UL Bulletin 94)		Class	HB	
ELECTRICAL PROPE	RTIES			
Electric Strength	Condition A			
(ASTM D149)		Volts/mil	185	

¹ NEMA LI-6: This temperature is a recommendation only, and based upon experience in various applications. The maximum operating temperature is dependent upon the application and should be investigated prior to use.

This data, while believed to be accurate and based on reliable analytical methods, is for informational purposes only. The terms and conditions of the agreement under which it is sold will govern any sales of this product. Data supplied above are "typical values"; not to be considered "specification values".

To assure the material's performance is adequate for a specific application; customers should verify, independent of Norplex-Micarta, performance characteristics of interest.

It is the responsibility of the users of this information to make sure that they have the latest version of this TDB, and are urged to contact Customer Service, or preferably our web site, www.norplex-micarta.com, to determine if information is the most current.

Specification writers: Contact Norplex-Micarta for specification values before submission.