

Convolute Rolled Tube Products - Dimensional & Tolerance Data

Norplex-Micarta Grade / NEMA Grade		Minimum & Maximum Inside Diameters and Tolerances								Minimum & Maximum Outside Diameters and Tolerances										
		Inside Diameter		Inside Diameter Tolerance (+/-) (For Inside Diameter Ranges Indicated)						Outside Diameter		Outside Diameter Tolerance Ground (+/-) (For Outside Diameter Ranges Indicated)			Outside Diameter Tolerance Lathe Turned (+/-) (For Outside Diameter Ranges Indicated)			Unfinished Minimum Target (+ only) (For Outside Diameter Ranges Indicated)		
				0.094" ≤ 0.749"	0.750" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"			24.001" ≤ 48.000"	0.156" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 9.000"	9.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"	9.000" ≤ 20.000"
Minimum	Maximum	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	(0.060")	Minimum	Maximum	1.999"	4.000"	9.000"	12.000"	18.000"	24.000"	48.000"	20.000"	Maximum		
RT130 / NEMA FR-4	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	52"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT130M / NEMA FR-4	0.312"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT130X / NEMA FR-4	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	49.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT500 / NEMA G-10	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT500F / NEMA G-10	0.187"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	49.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT500M / NEMA G-10	0.312"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT500X / NEMA G-10	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	49.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT504 / NEMA G-3, type	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT504F / NEMA G-3, type	0.187"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	49"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT505 / NEMA G-5	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	50.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT505F / NEMA G-5	0.187"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	48.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT507 / NEMA G-7	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT507F / NEMA G-7	0.250"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.313"	49.25"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT509 / NEMA G-9	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.563"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT509F / NEMA G-9	0.187"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	48.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT511 / NEMA G-11, type	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT511F / NEMA G-11, type	0.187"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	49.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT511M / NEMA G-11, type	0.312"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.375"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"

Convolute Rolled Tube Products - Dimensional & Tolerance Data

Norplex-Micarta Grade / NEMA Grade		Minimum & Maximum Inside Diameters and Tolerances								Minimum & Maximum Outside Diameters and Tolerances										
		Inside Diameter		Inside Diameter Tolerance (+/-) (For Inside Diameter Ranges Indicated)						Outside Diameter		Outside Diameter Tolerance Ground (+/-) (For Outside Diameter Ranges Indicated)			Outside Diameter Tolerance Lathe Turned (+/-) (For Outside Diameter Ranges Indicated)			Unfinished Minimum Target (+ only) (For Outside Diameter Ranges Indicated)		
				0.094" ≤ 0.749"	0.750" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"			24.001" ≤ 48.000"	0.156" ≤ 1.999"	2.000" ≤ 4.000"	4.001" ≤ 9.000"	9.001" ≤ 12.000"	12.001" ≤ 18.000"	18.001" ≤ 24.000"	24.001" ≤ 48.000"	9.000" ≤ 20.000"
Minimum	Maximum	(Built-up Mandrel)	(Built-up Mandrel)	(Built-up Mandrel)	(Built-up Mandrel)	(Built-up Mandrel)	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum				
RT521M / NEMA G-10	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	51"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT571 / NEMA G-10	0.500"	35.888"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.750"	36"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT310 / NEMA C	0.625"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.875"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT315	0.750"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	1.000"	58"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT342 / NEMA C	0.500"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.594"	56.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT360	2.000"	35.500"	N/A	N/A	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	2.500"	36"	N/A	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.175"	0.250"
RT370	2.000"	35.500"	N/A	N/A	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	2.500"	36"	N/A	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.175"	0.250"
RTB320 / NEMA LE	0.250"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.313"	55"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB320X / NEMA LE	0.187"	23.812"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	N/A	0.250"	24"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RTB320Z / NEMA LE	0.094"	0.938"	0.003"	0.004"	N/A	N/A	N/A	N/A	N/A	0.156"	1.562"	0.005"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
RTB324	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	50.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB324FR	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	50.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB326	0.375"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.438"	50.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RTB329	0.250"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.313"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.100"	0.150"
RT610 / NEMA X	0.187"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.250"	50"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT628 / NEMA XX	0.094"	23.812"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	N/A	0.157"	24.00"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT629 / NEMA XX	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	51.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT630 / NEMA XXX	0.094"	48"	0.003"	0.004"	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	0.156"	51.5"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.075"	0.125"
RT193PM	2.000"	48"	N/A	N/A	0.008"	0.010" (0.060")	0.030" (0.060")	0.040" (0.075")	0.060" (0.090")	2.250"	54.0"	0.005"	0.008"	0.025"	0.025"	0.030"	0.035"	N/A	0.175"	0.250"

Convolute Rolled Tube Products - Dimensional & Tolerance Data

Wall Thicknesses and Tolerances by Inside Diameter																							
Norplex-Micarta Grade / NEMA Grade	Inside Diameter		Minimum And Maximum Wall Thickness (For Inside Diameter Ranges Indicated)													Wall Thickness Tolerance (+/-) (Average Wall Thickness Of Individual Tube, Measured At Any Point On The Wall)							
	Minimum	Maximum	0.094" ≤ 0.186"	0.187" ≤ 0.249"	0.250" ≤ 0.374"	0.375" ≤ 0.499"	0.500" ≤ 0.624"	0.625" ≤ 1.249"	1.250" ≤ 1.999"	2.000" ≤ 2.999"	3.000" ≤ 4.874"	4.875" ≤ 8.999"	9.000" ≤ 23.999"	24.000" ≤ 29.999"	30.000" ≤ 48.000"	0.031"	0.032" ≤ 0.061"	0.062" ≤ 0.125"	0.126" ≤ 0.250"	0.251" ≤ 0.500"	0.501" ≤ 5.750"		
RT130 / NEMA FR-4	0.750"	48"	N/A	N/A	N/A	N/A	N/A	0.062" - 1.562"	0.062" - 2.000"	0.062" - 2.000"	0.062" - 2.000"	0.062" - 2.000"	0.094" - 2.000"	0.125" - 2.000"	0.156" - 2.000"	N/A	N/A	0.008"	0.009"	0.011"	0.013"	N/A	
RT130M / NEMA FR-4	0.312"	48"	N/A	N/A	0.031" - 0.250"	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.562"	0.031" - 1.500"	0.031" - 1.500"	0.047" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT130X / NEMA FR-4	0.094"	48"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.047" - 0.750"	0.062" - 0.750"	0.094" - 0.750"	0.125" - 0.750"	0.156" - 0.750"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT500 / NEMA G-10	0.750"	48"	N/A	N/A	N/A	N/A	N/A	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	N/A	N/A	0.008"	0.009"	0.011"	0.013"	N/A	
RT500F / NEMA G-10	0.187"	48"	N/A	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.047" - 0.750"	0.062" - 0.750"	0.094" - 0.750"	0.125" - 0.750"	0.156" - 0.750"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT500M / NEMA G-10	0.312"	48"	N/A	N/A	0.031" - 0.250"	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.047" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT500X / NEMA G-10	0.094"	48"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.047" - 0.750"	0.062" - 0.750"	0.094" - 0.750"	0.125" - 0.750"	0.156" - 0.750"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT504 / NEMA G-3, type	0.750"	48"	N/A	N/A	N/A	N/A	N/A	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	N/A	N/A	0.008"	0.009"	0.011"	0.013"	N/A	
RT504F / NEMA G-3, type	0.187"	48"	N/A	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.500"	0.031" - 0.500"	0.031" - 0.500"	0.031" - 0.500"	0.031" - 0.500"	0.047" - 0.500"	0.062" - 0.500"	0.094" - 0.500"	0.125" - 0.500"	0.156" - 0.500"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT505 / NEMA G-5	0.500"	48"	N/A	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.047" - 1.250"	0.062" - 1.250"	0.094" - 1.250"	0.125" - 1.250"	0.156" - 1.250"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT505F / NEMA G-5	0.187"	48"	N/A	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.047" - 0.250"	0.062" - 0.250"	0.094" - 0.250"	0.125" - 0.250"	0.156" - 0.250"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT507 / NEMA G-7	0.500"	48"	N/A	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.047" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT507F / NEMA G-7	0.250"	48"	N/A	N/A	0.031" - 0.250"	0.031" - 0.625"	0.031" - 0.625"	0.031" - 0.625"	0.031" - 0.625"	0.031" - 0.625"	0.047" - 0.625"	0.062" - 0.625"	0.094" - 0.625"	0.125" - 0.625"	0.156" - 0.625"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT509 / NEMA G-9	0.500"	48"	N/A	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.047" - 1.250"	0.062" - 1.250"	0.094" - 1.250"	0.125" - 1.250"	0.156" - 1.250"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT509F / NEMA G-9	0.187"	48"	N/A	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.031" - 0.250"	0.047" - 0.250"	0.062" - 0.250"	0.094" - 0.250"	0.125" - 0.250"	0.156" - 0.250"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT511 / NEMA G-11, type	0.750"	48"	N/A	N/A	N/A	N/A	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	N/A	N/A	0.008"	0.009"	0.011"	0.013"	N/A	
RT511F / NEMA G-11, type	0.187"	48"	N/A	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.031" - 0.750"	0.047" - 0.750"	0.062" - 0.750"	0.094" - 0.750"	0.125" - 0.750"	0.156" - 0.750"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A	
RT511M / NEMA G-11, type	0.312"	48"	N/A	N/A	0.031" - 0.250"	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.047" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A

Convolute Rolled Tube Products - Dimensional & Tolerance Data

Wall Thicknesses and Tolerances by Inside Diameter																							
Norplex-Micarta Grade / NEMA Grade	Inside Diameter		Minimum And Maximum Wall Thickness (For Inside Diameter Ranges Indicated)													Wall Thickness Tolerance (+/-) (Average Wall Thickness Of Individual Tube, Measured At Any Point On The Wall)							
			0.094" ≤ 0.186"	0.187" ≤ 0.249"	0.250" ≤ 0.374"	0.375" ≤ 0.499"	0.500" ≤ 0.624"	0.625" ≤ 1.249"	1.250" ≤ 1.999"	2.000" ≤ 2.999"	3.000" ≤ 4.874"	4.875" ≤ 8.999"	9.000" ≤ 23.999"	24.000" ≤ 29.999"	30.000" ≤ 48.000"	0.031"	0.032" ≤ 0.061"	0.062"	0.063" ≤ 0.125"	0.126" ≤ 0.250"	0.251" ≤ 0.500"	0.501" ≤ 5.750"	
	Minimum	Maximum																					
RT521M / NEMA G-10	0.375"	48"	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.031" - 1.500"	0.047" - 1.500"	0.062" - 1.500"	0.094" - 1.500"	0.125" - 1.500"	0.156" - 1.500"	0.006"	0.008"	0.008"	0.009"	0.011"	0.013"	N/A
RT571 / NEMA G-10	0.500"	35.688"	N/A	N/A	N/A	N/A	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2 x ID	0.125" - 2.250"	0.125" - 4.063"	0.125" - 9.500"	0.125" - 5.000"	0.156" - 3.000"	N/A	N/A	N/A	0.009"	0.011"	0.013"	N/A	
RT310 / NEMA C	0.625"	48"	N/A	N/A	N/A	N/A	N/A	1.562"	3.125"	3.125"	2.250"	5.750"	5.750"	5.750"	5.750"	5.750"	N/A	N/A	N/A	0.015"	0.020"	0.020"	N/A
RT315	0.750"	48"	N/A	N/A	N/A	N/A	N/A	1.562"	3.125"	3.125"	2.250"	5.750"	5.750"	5.750"	5.750"	5.750"	N/A	N/A	N/A	0.015"	0.020"	0.020"	N/A
RT342 / NEMA C	0.500"	48"	N/A	N/A	N/A	N/A	0.047" - 1.000"	0.047" - 1.562"	0.047" - 3.125"	0.047" - 3.125"	0.062" - 2.250"	0.062" - 4.250"	0.094" - 4.250"	0.125" - 4.250"	0.156" - 4.250"	N/A	N/A	0.015"	0.015"	0.020"	0.020"	N/A	
RT360	2.000"	36"	N/A	N/A	N/A	N/A	N/A	N/A	0.250" - 3.125"	0.250" - 3.125"	0.250" - 2.250"	0.250" - 5.750"	0.250" - 5.750"	0.250" - 5.750"	0.250" - 5.750"	N/A	N/A	N/A	N/A	0.020"	0.020"	N/A	
RT370	2.000"	36"	N/A	N/A	N/A	N/A	N/A	N/A	0.250" - 3.125"	0.250" - 3.125"	0.250" - 2.250"	0.250" - 5.750"	0.250" - 5.750"	0.250" - 5.750"	0.250" - 5.750"	N/A	N/A	N/A	N/A	0.020"	0.020"	N/A	
RTB320 / NEMA LE	0.250"	48"	N/A	N/A	0.031" - 0.250"	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.562"	0.031" - 3.125"	0.031" - 3.125"	0.047" - 2.250"	0.062" - 3.500"	0.094" - 3.500"	0.125" - 3.500"	0.156" - 3.500"	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - 0.011"	0.015" - 0.013"	N/A	
RTB320X / NEMA LE	0.187"	23.812"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.312"	0.031" - 0.312"	0.031" - 0.312"	0.031" - 0.312"	0.031" - 0.312"	0.047" - 0.312"	0.062" - 0.312"	0.094" - 0.312"	N/A	N/A	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - 0.011"	0.015" - 0.013"	N/A	
RTB320Z / NEMA LE	0.094"	0.938"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.312"	0.031" - 0.312"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - N/A	0.015" - N/A	N/A	
RTB324	0.375"	48"	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.047" - 1.250"	0.062" - 1.250"	0.094" - 1.250"	0.125" - 1.250"	0.156" - 1.250"	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - 0.011"	0.015" - 0.013"	N/A	
RTB324FR	0.375"	48"	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.047" - 1.250"	0.062" - 1.250"	0.094" - 1.250"	0.125" - 1.250"	0.156" - 1.250"	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - 0.011"	0.015" - 0.013"	N/A	
RTB326	0.375"	48"	N/A	N/A	N/A	0.031" - 1.062"	0.031" - 1.062"	0.031" - 1.250"	0.031" - 1.250"	0.031" - 1.250"	0.047" - 1.250"	0.062" - 1.250"	0.094" - 1.250"	0.125" - 1.250"	0.156" - 1.250"	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - 0.011"	0.015" - 0.013"	N/A	
RTB329	0.250"	48"	N/A	N/A	0.031" - 0.250"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.010" - 0.008"	0.010" - 0.008"	0.010" - 0.008"	0.011" - 0.009"	0.013" - 0.011"	0.015" - 0.013"	N/A	
RT610 / NEMA X	0.187"	48"	N/A	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.937"	0.031" - 0.937"	0.031" - 1.000"	0.031" - 1.000"	0.031" - 1.000"	0.047" - 1.000"	0.062" - 1.000"	0.094" - 1.000"	0.125" - 1.000"	0.156" - 1.000"	0.005"	0.006"	0.006"	0.007"	0.009"	0.011"	N/A	
RT628 / NEMA XX	0.094"	24"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.937"	0.031" - 0.937"	0.031" - 1.562"	0.031" - 1.562"	0.031" - 1.750"	0.047" - 1.750"	0.062" - 1.750"	0.094" - 1.750"	N/A	N/A	0.005"	0.006"	0.006"	0.007"	0.009"	0.011"	N/A	
RT629 / NEMA XX	0.094"	48"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.937"	0.031" - 0.937"	0.031" - 1.562"	0.031" - 1.562"	0.031" - 1.750"	0.047" - 1.750"	0.062" - 1.750"	0.094" - 1.750"	0.125" - 1.750"	0.156" - 1.750"	0.005"	0.006"	0.006"	0.007"	0.009"	0.011"	N/A	
RT630 / NEMA XXX	0.094"	48"	0.031" - 0.203"	0.031" - 0.218"	0.031" - 0.250"	0.031" - 0.937"	0.031" - 0.937"	0.031" - 1.562"	0.031" - 1.562"	0.031" - 1.750"	0.047" - 1.750"	0.062" - 1.750"	0.094" - 1.750"	0.125" - 1.750"	0.156" - 1.750"	0.005"	0.006"	0.006"	0.007"	0.009"	0.011"	N/A	
RT193PM	2.000"	48"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.125" - 1.500"	0.125" - 2.250"	0.125" - 3.000"	0.156" - 3.000"	0.187" - 3.000"	0.250" - 3.000"	N/A	N/A	N/A	N/A	0.040"	0.040"	N/A	